GK337

HIGH-SPEED CYLINDER ARM INTERLOCK CHAINSTITCH SEWING MACHINE
HOCHGESCHWINDIGKEITS-, FREIARM-ÜBERDECKNAHT-NÄHMASCHINE

TYPICAL

EN Technical Data

- Stitch type 605 (cover stitch)
- Max. sewing speed 6,000 spm.
- Differential drop feed
- Max. stitch length 3.6 mm
- Max. fabric clearance 6 mm
- Balance wheel 55 mm eff. Dia.
- Optimized thread guide for individual adjustment of each single needle thread
- Available needle distances: 4.8, 5.6 & 6.4 mm

Clearance under the arm
215×113 mm

Fully automatic lubrication system

Models
GK337 | 3 needle, 5 thread cover stitch machine for basic operations

Carton dimensions & gross weights for sewing head
58×45×63 cm, 48 kg

Specifications can differ depending on model.

DE Technische Daten

- Stichtyp 605 (Überdeckstitch)
- Max. Nähgeschwindigkeit 6.000 Stiche / Minute
- Differential-Untertransport
- Max. Stichlänge 3,6 mm
- Max. Durchgang unter dem Nähfuß 6 mm
- Handrad-Durchmesser effektiv 55 mm
- Optimierte Fadenführung zum individuellen Fadenabzug & Einstellen jedes einzelnen Nadelfadens
- Nadelabstände in 4,8 / 5,6 / 6,4 mm erhältlich

Durchgangsraum im Nähmaschinenarm
215×113 mm

Vollautomatisches Schmiersystem

Ausführungen
GK337 | 3-Nadel, 5-Faden Überdeckstich-Nähmaschine für Standard-Näharbeiten

Kartonmaße & Brutto-Gewichte für Nähkopf
58×45×63 cm, 48 kg

Angaben können je nach Ausführung abweichen.

		MAX				System		crossline			LMH
GK337	3×605	6,000	•	1:2.9 1-0.3	1.4–3.6	UY×128GAS 65-90	4.8, 5.6, 6.4	1×	5×	6	L/M

XI´AN TYPICAL EUROPE GmbH
Hertelsbrunnenring 9
D-67657 Kaiserslautern
Tel.: +49 (0)631 316019-0
Fax: +49 (0)631 316019-11

E-mail: sales@typical-europe.com
www.typical-europe.com

Certificate of the international ISO9001
Certificate of the ISO14001
Certificate of the international CE
Certificate for Ecolabelling Product
Certificate for Energy Conservation Product

GK337 // en/de – 05-2013