



GC6150



HIGH-SPEED LOCKSTITCH SEWING MACHINE WITH DROP FEED
DOPPELSTIPPSTICH-SCHNELLNÄHER MIT UNTERTRANSPORT

TYPICAL

GC6150

Technical Data

- Stitch type 301
- Max sewing speed 5,000 spm. (GC6150M)
- Max. stitch length 7 mm (GC6150H and GC6150B)
- Max. fabric clearance 13 mm with knee lever
- Balance wheel 70 mm eff. Dia.

Clearance under the arm

- 260×130 mm

Automatic oil pump lubrication system

Models

- **GC6150M**
Standard fast seamer for light to medium materials
- **GC6150H**
Fast seamer for heavy materials (needle bar stroke: 35 mm)
- **GC6150B**
Fast seamer for heavy materials and threads with large hook (needle bar stroke: 35 mm)

Carton dimensions and gross weights for sewing head

- 64×28×46 cm, 35 kg

Technische Daten

- Stichtyp 301
- Max. Nähgeschwindigkeit 5.000 Stiche / Minute (GC6150M)
- Max. Stichlänge 7 mm (GC6150H und GC6150B)
- Max. Durchgang unter dem Nähfuß 13 mm mit Kniehebel
- Handraddurchmesser effektiv 70 mm

Durchgangsraum im Nähmaschinenarm

- 260×130 mm

Automatisches Druckumlauf-Schmiersystem

Ausführungen

- **GC6150M**
Standard-Schnellnäher für dünne bis mittlere Faden- und Materialstärken
- **GC6150H**
Schnellnäher für dicke Materialstärken (Nadelstangenhub: 35 mm)
- **GC6150B**
Schnellnäher für dicke Faden- und Materialstärken mit großem Greifer (Nadelstangenhub: 35 mm)

Kartonmaße und Brutto-Gewichte für Nähkopf

- 64×28×46 cm, 35 kg

													
6150 -	M	•	5,000	•	4.0	134/DP×5 65-90	31.8	6/13	•		•	•	
	H	•	3,500	•	4.0	134/DP×5 100-160	35	6/13	•				•
	B	•	3,000	•	4.0	134/DP×5 100-160	35	6/13		•			•

Specifications can differ depending on model.
Angaben können je nach Ausführung abweichen.



XI'AN TYPICAL EUROPE GmbH

Hertelsbrunnenring 9
D-67657 Kaiserslautern
Tel.: +49 (0)631 316019-0
Fax: +49 (0)631 316019-11

E-mail: sales@typical-europe.com
www.typical-europe.com